

## **MENTOR 1**

Essentially a MENTOR 5 with a single 5" bass/midrange driver, the modest dimensions of the high performance MENTOR 1 mini-monitor makes it ideal on its own in smaller rooms or combined with a subwoofer in larger spaces.

Because DALI carefully matches drivers with low mass and rigid cones with low-loss crossovers with ideal impedance characteristics, MENTOR 1 does not demand a lot of current in order to play well. This allows MENTOR 1 to shine when accompanied by a typical affordably priced receiver or amplifier.

The versatile MENTOR 1 offers you wide-open installation options. In addition to stand or shelf mounting, a dedicated bracket is available for easy wall mounting.



## **SPECIFICATIONS**

Frequency range (+/- 3dB) [Hz]:	45,0 - 34.000,0
Sensitivity (2,83 V/1 m) [dB]:	86,0
Nominal impedance [ohms]:	6
Maximum SPL [dB]:	106,0
Recommended amplifier power [W]:	40,0 - 120,0
Crossover frequencies:	3.400/12.000
Hybrid tweeter module, Super high frequency drive	Ribbon
Hybrid tweeter module, High frequency driver:	Soft textile dome
Low frequency driver:	
Enclosure type:	Bass reflex
Bass reflex tuning frequency [Hz]:	47,0
Connection input(s):	Single wire
Recommended placement:	Stand;Shelf;On-Wall
Loudspeaker type:	Front;Rear;Surround
Loudspeaker type: Magnetic shielding:	Front;Rear;Surround No
1 21	No

## **AVAILABLE FINISHES**







**AWARDS** 

